F.A.U. RTE.	SECTION		COUNTY		TOTAL SHEETS	SHEET NO.
1602	Þ		COOK		38	2
STA. TO STA.						
FED. ROA	D DIST, NO. 1	ILLINOIS	FED.	AID	PROJECT	

## GENERAL NOTES

\*(0405-1 & 0506-2) RS-1 CONTRACT NO. 60B68

## INDEX OF SHEETS

## <u>DESCRIPTION</u> SHEET NO. TITLE SHEET INDEX OF SHEETS, STATE STANDARDS & GENERAL NOTES.

- EXISTING AND PROPOSED TYPICAL SECTIONS
- ROADWAY AND PAVEMENT MARKING PLANS 14-21 DETECTOR LOOP REPLACEMENT PLANS

SUMMARY OF QUANTITIES

- DETAILS FOR FRAMES AND LIDS ADJUSTMENT WITH MILLING
- PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT
- CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT
- BUTT JOINT AND HMA TAPER DETAILS 25
- TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS. INTERSECTIONS AND DRIVEWAYS
- TYPICAL APPLICATIONS: RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)
- DISTRICT ONE TYPICAL PAVEMENT MARKINGS
- TRAFFIC CONTROL AND PROTECTION OF TURN BAYS (TO REMAIN OPEN TO TRAFFIC)
- PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING
- TEMPORARY INFORMATION SIGNING 31
- 32-35 DISTRICT ONE STANDARD TRAFFIC SIGNAL DESIGN
- DISTRICT 1 DETECTOR LOOP INSTALLATION DETAILS FOR ROADWAY RESURFACING
- DRIVEWAY DETAILS >= 4.5M (15')
- DRIVEWAY DETAILS <= 4.5M (15')

000001-04 TYPICAL SYMBOLS, ABBREVIATIONS AND PATTERNS

STATE STANDARDS

442201-02 CLASS C AND D PATCHES

604001-02 FRAME AND LIDS, TYPE 1

604086-01 FRAME AND GRATE. TYPE 23

606001-03 CONCRETE CURB AND COMBINATION CONCRETE CURB AND GUTTER

701301-02 LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS

701311-02 LANE CLOSURE, 2L, 2W, MOVING OPERATIONS - DAY ONLY

701606-04 URBAN LANE CLOSURE, MULTILANE 2W WITH MOUNTABLE MEDIAN

701701-04 URBAN LANE CLOSURE, MULTILANE INTERSECTION

701801-03 LANE CLOSURE, MULTILANE 1W OR 2W CROSSWALK OR SIDEWALK CLOSURE

702001-06 TRAFFIC CONTROL DEVICES

886001 DETECTOR LOOP INSTALLATION

886006 TYPICAL LAYOUT FOR DETECTION LOOPS

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT (800) 892-0123 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE, AND GAS FACILITIES, (48 HOUR NOTIFICATION REQUIRED)

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES AND VILLAGES OF MIDLOTHIAN AND POSEN.

THE CONTRACTOR WILL NOT BE ABLE TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT THE WRITTEN PERMISSION OF THE DEPARTMENT.

BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT) IN ACCORDANCE WITH THE "BUTT JOINT AND BITUMINOUS TAPER DETAILS" SHEET INCLUDED IN THE PLANS UNLESS OTHERWISE SPECIFIED.

THE RESIDENT ENGINEER SHALL CONTACT MS. PATRICE HARRIS, AREA TRAFFIC FIELD ENGINEER, AT (708) 597-9800 A MINIMUM OF 72 HOURS PRIOR TO PLACEMENT OF FINAL PAVEMENT MARKINGS.

3 METERS (10 FEET) TRANSITION SHALL BE USED TO MATCH PROPOSED CURB AND GUTTER TO EXISTING CURB AND CUTTERS IN THE FIELD, UNLESS OTHERWISE SHOWN, THE TRANSITION SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PROPOSED ITEMS OF WORK SPECIFIED.

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC, THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1 1/2 INCHES WHERE THE SPEED LIMIT IS 45 MPH OR LESS, AND 1 INCH WHERE THE SPEED LIMIT IS 45 MPH, WITH WRITTEN APPROVAL FROM THE RESIDENT ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM OF 1:3 (V:H)

> ILLINOIS DEPARTMENT OF TRANSPORTATION INDEX OF SHEETS. STATE STANDARDS AND GENERAL NOTES SCALE: VERT. DRAWN BY DATE CHECKED BY

1013 011 9306 0130 3064a dan 12/21/2006 8 40 16 AM Hagr-en.html